

DW-5058

Recessed Access door for 5/8" drywall,
Drywall Panel Door

Application

- Designed to provide access in walls and ceilings, while maintaining an invisible, architecturally pleasing appearance

Product Features

- Designed for installation in 5/8" drywall
- Aluminum Extrusion Door & Frame
- Powder Painted
- Dust seal gasket
- Concealed Touch latch

DW-5058 Access Door Specifications:

Material: Aluminum extrusion with drywall fitted in door panel
 Door Frame: Aluminum extrusion 6063-T6 recessed to provide similar edge to drywall bead to allow for finishing of wall or ceiling surface.

Hinge: Wing hinge allows door panel to open to 90 degrees, and also allows for door panel to be removed from frame. Safety chain installed on door & frame for safety.

Gasket: Dust seal gasket

Standard Latch: Concealed Touch Latches

Optional Latches/Locks: Screwdriver operated cam latch, allen head cam latch, spanner head cam latch, cylinder lock & key.

Finish: Powder Painted White



STANDARD SIZES (other sizes available upon request)

| Nominal Door Size W&H | | Weight per Door | |
|-----------------------|-----------|-----------------|-----|
| inches | mm | lbs. | kg. |
| 8 x 8 | 203 x 203 | 1.5 | 0.7 |
| 12 x 12 | 305 x 305 | 2.0 | 0.9 |
| 16 x 16 | 406 x 406 | 5.0 | 2.3 |
| 18 x 18 | 457 x 457 | 6.0 | 2.7 |
| 24 x 24 | 610 x 610 | 12.0 | 5.5 |
| 24 x 36 | 610 x 914 | 21.0 | 9.5 |

Wall opening is normal door size plus +1/2" (12mm)
 For detailed specifications see submittal sheet

