

ENCORE

medium texture

AVAILABLE
IN STOCK

40% RECYCLED*
CONTENT

- LEED®
- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics



Encore with XL32 24mm suspension system

Encore ceilings offer an economical option for general commercial use areas.

KEY SELECTION ATTRIBUTES

- Economical
- High light reflectance
- Humidity resistant – RH95-49°
- BioBlock® Paint resists the growth of mold and mildew

COLOR



White
(WH)

VISUAL SELECTION

Description	Item No.	Dimensions
ENCORE		
24mm Lay-in	1932	625 x 1250 x 13mm


** Resists up to 95% of relative humidity at a indoor air temperature of 49°C

PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability
NRC	CAC	Lightbulb icon	Anti-Mold & Mildew icon	Water drop icon	Certified Low VOC Emissions icon	Durability icon
0,50	35	0,86	BioBlock	RH95-49°**		Std.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled)

ASTM E1264 Classification
Type III, Form 1, Pattern E I
Fire Class A

Thermal Coefficient
K: 0,061 w/m

Humidity/Sag Resistance
RH95-49° ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title

24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Weight
3,4 kg/m²

Recommended Suspension System
XL32 24mm suspension system

*The recycled content of products is subject to change. This information should be verified with your Armstrong Ceilings representative.