

KITCHEN ZONE™

Square Lay-in
smooth texture



Kitchen Zone™ 24" x 24" panels with Prelude® XL® 15/16" suspension system (Pgs. 458-459)

A better option to vinyl-covered gypsum, this panel offers a lower cost, lighter weight, more pieces per carton, and meets USDA/FSIS guidelines.

KEY SELECTION ATTRIBUTES

- Easier to cut with less dust
- Recyclable through Armstrong Recycling Program
- Brighter visual with 20% more light reflectance than vinyl-covered gypsum
- Durable – Water-repellent, Washable, Scratch-resistant, Soil-resistant
- Smooth surface meets USDA/FSIS guidelines for use in food processing areas
- 30-Year Limited System Warranty against visible sag, mold, and mildew

TYPICAL APPLICATIONS

- Kitchen/food preparation areas
- Laboratories
- Cafeterias
- Lavatories/restrooms

COLOR



White
(WH)

DETAILS



1. Kitchen Zone™ Lay-in
2. Kitchen Zone™ Lay-in with Prelude® 15/16" suspension system

KITCHEN ZONE™

Square Lay-in
smooth texture

GREENGUARD
Gold Certified
(details below)

UP TO **36%** RECYCLED CONTENT




Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/extended producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

LOCATION DEPENDENT

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 474-478 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)
KITCHEN ZONE™			
15/16" Square Lay-in	1	673	24 x 24 x 5/8" 
			
	1	672	24 x 48 x 5/8" 

PERFORMANCE SELECTION

Dots represent high level of performance.


\$\$\$

NRC	+ CAC	=	Total Acoustics ¹	Fire Performance	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Water Repel	Wash	Scratch	Soil	Recycled Content	Recycle Program	30-Yr Warranty
N/A	33	-	Class A	0.89	•	•	•	•	•	•	•	•	Std	•	•
N/A	33	-	Class A	0.89	•	•	•	•	•	•	•	•	Std	•	•

¹ Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS

15/16"



Prelude®

PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 surface burning characteristics.
Flame Spread Index 25 or less. Smoke Developed Index 50 or less.

ASTM E1264 Classification

Type IX, Form 2, Pattern G
Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

VOC Emissions

GREENGUARD Gold Certified

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value

R Factor - 1.6 (BTU units)
R Factor - 0.28 (Watts units)

Application Consideration

Not designed for use in close proximity to commercial grease ducts.

PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com

Cleaning Recommendations

To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface. To disinfect panel, lightly spray surface and wipe clean with a clean, white cloth. Acceptable colorless disinfectants include:

- Sodium hypochlorite
- Hydrogen peroxide
- Quaternary ammonium

Weight; Square Feet/Carton

672 - 0.67 lbs/SF; 96 SF/ctn
673 - 0.82 lbs/SF; 64 SF/ctn

Minimum Order Quantity

1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/commercial
(search: kitchen zone)
BPCS-4667-718

LEED® is a registered trademark of the U.S. Green Building Council
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2018 AWI Licensing LLC Printed in the United States of America

Armstrong®
CEILING & WALL SOLUTIONS

327

MINERAL FIBER