


Submittal Sheet

| STOCK# | NAME | PCS/BOX |
|--------|------------------------|---------|
| #8158 | 7/8" Angle 8' (White) | 63 |
| #8158M | 7/8" Angle 8' (White) | 10 |
| #8159 | 9/16" Angle 8' (White) | 63 |
| #8178M | 7/8" Angle 8' (Black) | 10 |



Flex Grid Angle

Description: Trim-Tex Flex Grid Angle is designed to finish an acoustical ceiling terminating at any curved wall or surface.

Advantages: Made from rust proof, dent resistant PVC to reduce jobsite and handling damage. Does not contain cellulose, a potential food source for mold.

Limitations: Product is designed for interior use.

Applicable Standards: Rigid PVC products made by Trim-Tex achieve a Class A rating for flame spread and smoke developed when tested under ASTM E84.

Surface Characteristics: Trim-Tex products are made from PVC. PVC does not support combustion and is self extinguishing when the source of flame or heat is removed.

Installation: Trim-Tex recommends following established acceptable industry standard installation methods. Detailed installation instructions can be found at www.trim-tex.com.

Finishing: Always use a high quality paint.

Accessories: 847 Spray Adhesive and Safety Products distributed by Trim-Tex.

| Job Name | | |
|----------------------------------|--|--|
| Contractor | | |
| Date | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Approvals (Signatures or Stamps) | | |
| Approvals (signatures or stamps) | | |
| | | |
| | | |
| | | |
| | | |
| | | |