

S-543 Commercial Sheet Flooring & LVT Premium Plus Adhesive



CAUTION

S-543 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Commercial Vinyl-Backed
- Commercial Heterogeneous and Inlaid
- Commercial Luxury Vinyl Tile
- Residential LVT Plank

DESCRIPTION:

Type:	Water-based/synthetic polymer
Color:	White; contains visible taggants
Taggants:	50% Yellow and 50% Orange
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	225–275 sq. ft. (25–30 sq. yds.) /gal (21–26 sq. m)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates — Set-in-wet: Minimum 10–20 minutes Nonporous substrates — Dry-to-touch: 30 minutes or more
Working Time:	Up to 8 hours (May vary based on job conditions, substrates, temperature and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet — clean, white cloth with neutral detergent and water Dry — clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors and suspended wood
Advantages:	Increased working time High bond strength Can be used in all commercial vinyl-backed sheet flooring applications Strong initial grab for “set-in-wet” sheet installations Superior moisture and alkali resistance Anti-fungal/mold protection